

Roll-On Connector

Thru-Tubing Technology | Product Code | WT - 1304

Features

- Attaches a BHA to the coil
- Available for all coil sizes.
- One-piece design
- Reusable connector fitted with standard O-rings
- Robust and cost effective
- Three O-ring grooves
- Three crimping grooves

Benefits

- Easy to redress in the field
- Provides added security in high-pressure applications

The Roll-On Connector with one-piece design provides a robust, cost effective means of attaching a BHA to the coil.

The one-piece design incorporates three O-ring grooves providing added security in high-pressure applications, while three crimping grooves give improved tensile strength.

The connectors can be supplied with standard through-tubing tool joints or cut to suit customer requirements. The connector is reusable and furnished with standard O-rings making it extremely easy to redress in the field.

The Roll-On Connector is available for any combination of coil tubing and thread size.



Roll-On Connector / Product Code WT-1304

Coil Tubing OD in inches	1-1/4"	1-1/2"	1-3/4"	2"	2-3/8"	2-7/8"
Wall Thickness	TBA	TBA	TBA	TBA	TBA	TBA
OD in inches	TBA	TBA	TBA	TBA	TBA	TBA
End Connection	1" AMMT	1-1/4" AMMT	1-1/4" AMMT	2-3/8" PAC	2-3/8" PAC	2-3/8" PAC
ID in inches	0.500	0.688	0.750	1.000	1.000	1.375
Tensile Strength	23,870	38,390	69,080	77,440	178,860	165,110
Length in feet	0.67	0.67	0.67	0.67	0.67	0.67
Working Pressure in Psi	10,000	10,000	10,000	10,000	10,000	10,000

Other sizes, end connections and materials available on request. Properties quoted for standard service materials. All ct sizes can be accommodated.