www.hunting-intl.com/titan



## **Plug Shoot Cartridge Firing Head** Titan Division | Perforating



Hunting is reducing the toolstring footprint eliminating wiring to maximize reliability and performance.

Hunting has improved the traditional plug and shoot toolstring by combining the plug/shoot adapter, quickchange adapter, and firing head into one component - the Plug Shoot Cartridge (PSC) Firing Head. Hunting's PSC Firing Head utilizes a ControlFire<sup>®</sup> Cartridge to eliminate wiring the plug switch.

#### Features


- Plug Shoot Cartridge contains the plug-switch, pressure bulkhead, and electric contacts
- Reduces the number of seal points from five to two
- Reduces toolstring footprint by ~10 inches [25 cm]

### Benefits

- Eliminates wiring
- Reduced risk of seal point leaks
- No contacts kit or rebuild required

## Reduce Three Components to One

Traditional Version




New Version

www.hunting-intl.com/titan



#### Easy to Assemble



#### Assembly Components

ltem Number	Part Number	Description				
2010-275-200		Assembly Components				
1	2010-275-201	#10 PSC Firing Head: 2 3/4" Exp. Gun				
2	HTS-PSA-012	GO Style Igniter Holder: # 10				
3	HTS-PSA-013	Female Bull Plug: # 10				
Reference Parts						
4	0111-222-V95	O-Ring				
5	HTS-PSC-000	Plug Shoot Cartridge Assembly				
6	0362-000-369A	EB Switch Sub with Port				
7	9400-EBTW-WG	EB Feed Thru with Ground				
8	9400-EBRN-WR	Retainer Nut with Rivet				

Note: The PSC Firing Head assembly includes parts 1-3. All other parts are for reference. Components for a 2.75" O.D. assembly with #10 PSC Firing Head is shown for example.

#### Use with the T-Set® Family of Setting Tools

		T-Set <sup>®</sup> Family of Setting Tools			
Assembly Part Number	Description	#10 Style	#20 Style	3-1/2" Shorty	3-5/8" Compact
2020-312-200	3-1/8" #20 Style PSC Firing Head	Ν	Y	Y*	Υ†
2020-337-200	3-3/8" #20 Style PSC Firing Head	Ν	Y	Y*	Υ†
2010-275-200	2-3/4" #10 Style PSC Firing Head	Y	Ν	Y**	Y‡
2010-312-200	3-1/8" #10 Style PSC Firing Head	Y	Ν	Y**	Y‡

(^') requires adapter WST-5321-232; (Y\*\*) requires adapter WST-5321-132 (Y') requires adapter WST-3625-133; (Y\*) WST-3625-132





Each PSC Firing Head is compatible with T-Set setting tools.

# Complete Assembly Specifications

		Specifications				Additional Components
Part Number	Description	Outside Diameter (in)[mm]	Overall Length (in)[cm]	Shoulder Length (in)[cm]	Weigth (lb)[kg]	Igniter Holder
2020-312-200	3-1/8" Plug Shoot Cartridge Firing Head Assembly for #20 TSET	3.13 [79]	15.03 [38.18]	11.06 [28.09]	24.3	HTS-PSA-022
2020-337-200	3-3/8" Plug Shoot Cartridge Firing Head Assembly for #20 TSET	3.38 [86]	15.03 [38.18]	11.06 [28.09]	24.3	HTS-PSA-022
2010-275-200	2-3/4" Plug Shoot Cartridge Firing Head Assembly for #10 TSET	2.75 [70]	15.22 [38.66]	11.50 [29.21]	15.2	HTS-PSA-012
2010-312-200	3-1/8" Plug Shoot Cartridge Firing Head Assembly for #10 TSET	3.13 [79]	14.95 [37.97]	11.23 [28.52]	18.7	HTS-PSA-012

Note: The Plug Shoot Assembly ships with an igniter holder and contact kit

For more information contact your Titan Division sales representative today! Or visit us at: www.hunting-intl.com/titan

#### Contact Information

Sales sales.titan@hunting-intl.com

Support support.titan@hunting-intl.com Perforating Pampa, TX USA Milford, TX USA Calgary, AB CAN Instruments Pampa, TX USA Wichita Falls, TX USA Houston, TX USA Energetics Milford, TX USA

Distribution

Hunting's distribution centers are strategically placed globally. For more information, visit us at: www.hunting-intl.com/titan