

Otis® J Running Tool

Slickline Downhole Tools

The Otis J Running Tool sets the type J, E, P, F and L Otis locking mandrels in the Otis type J, E, P, F and L landing nipples.

The Otis J running tool consists of a top sub complete with fishing neck, sucker rod pin connection, shear pin holes for retaining the lock mandrel and an internal thread to accommodate a prong.

Lock mandrels being deployed by the J running tool are located and set by downward jarring. Once the lock mandrel has been set in the nipple, subsequent upward jarring will shear the tangential pins allowing the release of the J running tool.

Contact your local Hunting Sales Representative for further technical details

Hunting J Running Tools are available with various connections to suit customer requirements.

HEAVY DUTY RELEASABLE OVERSHOT					
Used to Run	Nominal Size	Maximum Size (OD)	Fishing Neck on Tool	Fishing Neck Will Engage	Connection
Type J, E, P, F and L Lock Mandrels	0.750"	0.690	0.687"	0.413"	1/2" 13 UN
	1.000"	0.810"	0.687"	0.581"	1/2" 13 UN
	1.250"	1.120"	1.000"	0.812"	5/8" 11 UN
	1.500"	1.190"	1.187"	1.000"	15/16" 10 UN
	2.000"	1.620"	1.375"	1.625"	15/16" 10 UN
	2.500"	2.000"	1.750"	1.445"	15/16" 10 UN
	3.000"	2.500"	2.313"	1.937"	1 1/16" 10 UN
	4.000"	3.500"	2.313"	2.875"	1 1/16" 10 UN

Spares components are available. Please specify part and assembly part number or part number if known.

