

## Otis® R Running Tool Slickline Downhole Tools

The Otis® R Running Tool is designed to deploy and set sub surface flow control devices equipped with R and RN® lock mandrels, landing in corresponding selective or no-go landing nipples.

The running tool can be set up to run devices either in selective or non-selective mode.

By choosing the selective mode, devices can be run through landing nipples (R type – non no-go nipples) of the same size and type, before the operator performs a manipulation at the desired location nipple and sets the device.

In the non-selective mode, the lock mandrel will locate the first corresponding nipple.

Contact your local Hunting Sales Representative for further technical details

**Hunting ‘R’ Running Tools are available with various connections to suit customer requirements**

OTIS® R® RUNNING TOOL			
Nominal Size	Actual Size (OD)	Fishing Neck	Connection
1.375"	1.281"	1.000"	5/8" 16 UN
1.500"	1.469"	1.187"	15/16" 10 UN
1.710"	1.641"	1.187"	15/16" 10 UN
1.781"	1.750"	1.375"	15/16" 10 UN
1.875"	1.750"	1.375"	15/16" 10 UN
2.000"	1.938"	1.375"	15/16" 10 UN
2.125"	2.062"	1.375"	15/16" 10 UN
2.188"	2.172"	1.750"	15/16" 10 UN
2.313"	2.172"	1.750"	15/16" 10 UN
2.562"	2.172"	1.750"	15/16" 10 UN
2.875"	2.840"	2.313"	1 1/16" 10 UN
3.500"	3.125"	2.313"	1 1/16" 10 UN
3.437"	3.406"	2.313"	1 1/16" 10 UN
3.688"	3.625"	2.313"	1 1/16" 10 UN
4.000"	3.938"	2.313"	1 1/16" 10 UN
4.125"	3.938"	2.313"	1 1/16" 10 UN
4.313"	4.281"	2.313"	1 1/16" 10 UN

Spares components are available. Please specify part and assembly part number or part number if known.

