


Pump Bailers

The Hunting Sand Pump Bailer is designed to remove sand and other debris, which may have settled on top of any sub-surface control within the well, preventing retrieval of the control by regular wireline operations.

The sand pump bailer operates on a simple lift pump and piston principle, similar to a bicycle pump. Various shoe sizes and types are available (see below).

Hunting Sand Pump Bailers are available in various sizes with extension barrels and connector subs where applicable. All Hunting pump bailers are supplied with industry standard pin connections complete with fishing neck.

When ordering, please specify Hunting product number, along with type and size of bottom shoe.

 The sand pump bailer operates on a simple lift pump and piston principle, similar to a bicycle pump.

Bailer Shoes

Hunting Pump Bailers are available with the following types of bottom shoe, sized to suit operational requirements:

- Ball shoe
- Flapper shoe
- Chisel bottom (ball)

PUMP BAILERS			
Size OD	Fishing Neck	Connection	Part Number
1.250"	1.187"	15/16-10	050TSB125000
1.500"	1.375"	15/16-10	050TSB150000
1.625"	1.375"	15/16-10	050TSB162500
1.750"	1.375"	15/16-10	050TSB175000
2.000"	1.375"	15/16-10	050TSB200000
2.250"	1.375"	15/16-10	050TSB225000
2.500"	2.313"	1 1/16-10	050TSB250000
3.000"	2.313"	1 1/16-10	050TSB300000
3.500"	2.313"	1 9/16-10	050TSB350000



Wireline Operations - Slickline Tools

